


21.5" PRO TOUCH SERIES

LINQ Pro Touch Series tablets combine powerful performance with a slim form factor to deliver interactive digital experiences. Designed for continuous commercial use, the tablets use AC-DC power, eliminating the need for battery power and making them ideal for fixed applications such as digital signage, self-service kiosks and interactive guided selling.

Equipped with a front facing camera and integrated sensors, the tablets enable consumer detection, identify audience demographics and can deliver highly personalized customer experiences. A variety of I/O options provide the versatility to connect multiple accessories and peripherals to customize your solution. The robust content management platform provides integrated media scheduling and application, content and device management across diverse locations.







COMMERCIAL-GRADE RELIABILITY

Operate in rugged and demanding environments without interruption



ALL-IN-ONE INTELLIGENT SCREEN

Combines powerful performance with a slim design



INTEGRATED HARDWARE AND SOFTWARE

Manage content updates and devices across diverse locations

ADDITIONAL FEATURES

- · Variety of sizes: 11.6", 15.6", 18.5", 21.5", 32", 43" and 55"
- · Flexible Mounting Options: Portrait or Landscape with VESA standard mount fixations
- · Accessory Integration: Scanners, card readers and more

TECHNICAL SPECIFICATIONS



Description Model Description Power Operating System	Standard LINQ 21.5" Pro Input: 100-240' Output: 12V D Android 8.1 / Li 2 GB Dual-channel DDR3-1600 (800 MHz)	V~50/60Hz AC C Screw Lock
Power	Input: 100-240' Output: 12V D Android 8.1 / Li 2 GB Dual-channel DDR3-1600 (800 MHz)	V~50/60Hz AC C Screw Lock nux 4.4 Kernel
	Output: 12V D Android 8.1 / Li 2 GB Dual-channel DDR3-1600 (800 MHz)	C Screw Lock nux 4.4 Kernel
Operating System	2 GB Dual-channel DDR3-1600 (800 MHz)	
		(CD Dual abandal DDD7 1600 (000 MHz)
Memory	Civ. sava Daal	4 GB Duai-channel DDR3-1600 (800 MH2)
CPU	Six-core Rockchip RK3399 ARM 64-bit processor, up to 2.0 GHz Dual-core ARM Cortex-A72 and Quad-core ARM Cortex-A53	
GPU	ARM Mali-T860 MP4 Quad-core GPU	
Storage	32 GB high-speed eMMC 5.1	64 GB high-speed eMMC 5.1
Display Panel	21.5" IPS, 1920 x 1080, 500 Nits Brightness, 89° Viewing Angle	
Touch Panel	10-point capacitive touch panel	
HDMI	One HDMI 2.0 input, one HDMI 2.0 output	
Auxiliary Audio	One 3.5 mm, One Toslink S/PDIF	
Speakers	Two 5W Speakers	
Network	Gigabit Ethernet RJ45, 2.4/5 GHz Dual-band Wi-Fi (IEEE 802.11a/b/g/n/ac), Bluetooth 4.0, 4G LTE (optional)	
Antenna	One WiFi/Bluetooth, One 4G LTE	
USB	Five USB 2.0 (One service), One UART Serial	
Front Camera	8 Megapixel	
Other I/O	Buttons: Home/Recovery, Vol +/-, Brightness +/-, Reset, Custom (*) SD Card, 4G module and SIM card bay	
Mount	VESA 100 x 100 mm and VESA 75 x 75 mm	
Dimensions	532.1 x 328.6 x 36.7 mm / 20.95 x 12.94 x 1.45 in	
Net Weight	5.94 kgs /13.10 lbs	
Enclosure	Metal casing with aluminum frame	
Storage Femperature	-15° - 65° C / 5° - 149° F	
Working Femperature	0° - 50° C / 32° - 122° F	
Storage/Working Humidity	10 - 90% Non-condensing	
Warranty ¹	1 year included, extended warranty available	
Optional Upgrades ²	4G LTE: Quectel EG25-G LTE Module with internal SIM card slot	

¹Extended warranties must be added at time of purchase

²4G Module and SIM card not included

